

BQ-P60

Superior binding strength and compact desktop design make this the ultimate office binder



Features of BQ-P60

- **Easy operation**: The display Indicator lamps on the operating panel guide you through the simple operating steps
- High productivity: 180 books/hour
- **Professional binding quality**: A cover is glued to the book spine and then clamped to create an attractive finished appearance
- **Flexible binding styles**: Choose from three different binding styles -- Binding with cover, Binding with tape, or Pad binding
- **Comfortable operation**: An integrated smoke extractor and filter system is a standard feature to clean the air and remove any glue odors from office environments
- Eco-friendly: Low-temperature glue and, eco-mode, reduces power consumption

High quality binding gives you a lead in making materials, such as for presentations.

■ Clamper Section ■

The book block is firmly clamped, to produce a professional quality book up to 25 mm thickn.

■ Nipping Section ■

Nipping strength is adjusted automatically according to the binding style resulting in document quality not found in other tabletop binders.





■ Glue Application Section ■

Amount of glue can be adjusted by dial, depending on the thickness of the book. Smoke extractor removes glue odors from the office for comfortable operation.



■ Operation Panel Section ■

To start, simply choose the desired binding style, insert the book block, and follow the procedures indicated by the LED lamps. The machine goes to Eco-mode automatically after certain period if the machine is not used.



■ Cover Insertion Section ■

Users original cover can be used. Binding with tape is also available. Tape widths of 30 mm to 40 mm can be used.

Easy Operation

Professional documents are finished fast With simple push-button operation.



Choose the binding style and insert the book block.



Press the start button.



Insert a cover, then press the start button.



The book is finished!

■ Three Different Binding Styles are Supported







Binding with tape Simple book bound with cloth tape.



Pad binding
Simple binding used
for making memo-pads.

BQ-1 00 Major opecinications	
Binding Style	Binding with cover sheet, Binding without tape, and Padding
Book Size	Max. 315 x 210 mm (12.4" x 8.2")
(Top-Bottom x Fore-edge)	Min. 210 x 148 mm (8.3" x 5.9")
Book Thickness	Max. 25 mm (0.9")
Cover Size	Max. 315 x 445 mm (31.4" x 17.5")
(Top-Bottom x Fore-edge)	Min. 210 x 297mm (8.3" x11.7")
Cover Weight Range	82 to 210 gsm (22 to 60 lb)
Glue tank Temperature	130 to 150 °C (266 to 302 degrees Fahrenheit)
Production Speed	Max. 180 books/hr.
Power Supply	Single Phase 115 V, 50 / 60 Hz
	Single Phase 230 V, 50 / 60 Hz
Power Consumption	1.05 kW / 1.15 kW (115 V, 50 / 60 Hz)
	1.1 kW (230 V, 50 / 60 Hz)
Machine Dimensions	600 (W) x 615 (D) x 270 (H) mm (23.7" x 24.3" x 10.7")
Machine Weight	48 kg (105.9 lbs)

BO-P60 Major Specifications

Consumables

Hotmelt glue – HM-302 Color cover

hot-melt glue.

- A4 / B5 size with / without die cut window each 5 colors
- A4 size suitable sheets for laser printer ... 2 colors
 Clear cover A4 / B5 each 3 colors
- Glue-backed cloth tape 6 colors
- * Width 30 mm (1.18") : Black

Width 40 mm (1.57"): Dark Blue, Orange, Sky Blue, White, Red, Black



Distributed by

^{*}The machine design and specifications are subject to change without notice.