


STERLING DIGIBINDER PLUS SG

The STERLING DIGIBINDER PLUS SG has created a new standard for on demand perfect binding. Never has a perfect binder been able to create books of such quality with automatic set up at such an affordable price. It has set the bar high for all perfect binders to follow.



Bind two sheets to two inches thick. The unique, heavy duty roughing blade allows for the binding of offset stock, coated stock, and stock with oil based or wax based inks.

Twin glue rollers ensure an even glue application as does a third, metering roller to smooth out the glue. The machine also includes a separate, side glue pot, allowing you to control the amount of side glue under a hinge score. Bind perfectly square backed books or pads.

Good for runs of one offs, five hundred, or five thousand, the user friendliness of the Sterling® Digibinder will astound you.

With no jam ups and no set ups, one touch perfect binding is here, with...

THE STERLING DIGIBINDER PLUS SG.





STERLING DIGIBINDER® PLUS SG FEATURES



AUTO CLAMP

The clamp adjusts automatically between two sheets and 2 inches. Both the clamp and nipper are pneumatic, run by the supplied silent compressor.



HEAVY DUTY NOTCHING

The Digibinder Plus sports our heaviest duty roughing blade, designed to grind deeper into the spine to facilitate the binding of problems stocks.



WASTE REMOVAL

The Digibinder Plus SG includes a vacuum waste removal system. This facilitates the ability to rough and notch deeper to maximize the strength of the book.



SIDE GLUING

The Digibinder Plus SG sports a separate side glue pot, allowing for greater side glue control for hinge covers.



NIPPER CONTROL

The distance that the nipper travels can be set to produce more square backed books. The dwell time can be set up to 3 seconds. The nipper height can also be adjusted.

STERLING DIGIBINDER PLUS

FEATURES



STAND/SAFETY COVER

The Digibinder Plus SG includes a stand on casters. The compressor and vacuum are installed in the stand. A safety cover disables the machine when in the open position.

Ask about our Digiglue and iglue for coated stock.

SPECIFICATIONS Up to 300 BPH Speed: Maximum Book Thickness: 2" / 50mm Minimum Book Thickness: 2 sheets Maximum Spine Length: 12.5" / 32cm Maximum Cover Size: 13.4 x 30.75"/34 X 78cm 220V 1 Phase 12 Amps/2.3kw Power: 35" L X 54.4" W X 52" H Dimensions: 89 L X 138 W X 132cm H Weight: 575 lbs. / 261 kg.

