



**DF0906-MT** 

**DF1007-MT** 



The Graphic Whizard digital flatbed cutter line is the only one in the market of automatic plotters with Interchangeable Tools for specific and professional processes to handle not only prototyping, but also for small production. Capable of handling plasticized prints (up to 10mm with the oscillating tool) sheets are automatically managed allowing for unparalleled operator freedom. Feed, cut, crease, perf, and more on materials such as; paper, cardboard, corrugated, light PVC, FOAM, KT Carton, coupled, special foil, polypropylene sheets, vinyl, ABS, magnetic adhesives. Interchangeable tools allow for cutting, kiss-cutting, creasing and perforation.

## **Applications:**

Short run die-cutting





**Textiles** 



Labels and Vinyl





Packaging



The CONTROL CENTER Software will directly drive the Cutter for the job you want to perform, and if you have already created it, the setup will take place by automatically reading the supplied barcode. Accuracy is ensured by the mark reader that controls the head to achieve perfection every time.

				=					
Advanced parameters natting Springs notch width	5.00000	Facines notch angle	[75 000000						
Sinisus area of patters.	40.000000	Remark conflictment	350.000000						
I deparation of outline act.	Detection or	f Trabaped not   Buister	netch type						
" Road principal point	I' Bread retlin								
T Beset test	I The oputer	test   Detecti	m of grain	200000					
I direction flip piece	I I direction			( -	CONTRACT OF		-	1	
T Retation pattern pieces	Retation ungle								
I' Adjustment of the direct:									
I Ignore the short oner li-	SF Adjustment	of start point [ Forced	desing of extline	1					
Title of short inner line	7 000000	Reight of short issuer I	ina [7.000000	100					
Theatify round help us we		Back tops	Eross awk w.	-					
Diseaser of round help	8.00	Back distrator	0.00	1000		1	-		Alle
T Delate coincidence line Buf natting				1000					
F Ignore the layer that in			r grading var						
The Between the prince quarties of Ignore cut line Theory by Larges	Egure ter		m served or flip emertation test						
I Ignere out line	Igure ter							w) Br	
Tigore on line Tigore by Layers Fath:	Igure ter			Athened			- Book o		
Igner on him Import by Layers Fath:   D   MCDity sciff.   Engli parameters satting	Igure ter		emortation test	Advanced	1		Florick, co		orte cording to col
Igners out line Import by Layers Fach:   D Militar-scapill Engel parameters natting Section notch length	Egent net     2009   40 agt	line Figure	emortation test	Advanced That setts	]		Facial co		
Park: Discrip-sorts	Equate test	Time   Ignere  Timinum coincident proc  Import curve precision	manufation test	Short settle	person		Florida co		
Egoro cut him  Depart by Legors  Path: D Willing scalling Egori permeters satting Maximum noted length  D Optimization of curve poi	Equate test	Time   Ignere  Timinum coincident proc  Import curve precision	manufation test	that settle	person	•	Fred o		
I Ignore out him Inport by Layers Path: D Willia-scipt. Input parameters satting Section and himself. I Optimization of curve poi Identifications and him Identify number has	Equate test	Time   Ignere  Timinum coincident proc  Import curve precision	manufation test	- Short natto Short Proportion	person		Front of		
I Igner out him Import by Layers Path: D-WEITE-BEILL Imput parameters setting Homel parameters setting D-Deletions south length D-Deletions out are point I descript nucleon has Import any setting Depart any setting	Eguere see	Ninism criteridan pro- Import curve precision of Y-chaped and	manufation test	Mail satts Mail Proportion	person		Front of		
I Igner out him Import by Layers Path: D-WEITE-BEILL Imput parameters setting Homel parameters setting D-Deletions south length D-Deletions out are point I descript nucleon has Import any setting Depart any setting	Eguere see	Ninism retardant proc Superi correspondant of Y-shaped and	esconistico test	Whit setts that Proportion Out tops of Auto	(C. IIII. (Ex)	•	French en		
In Ignore out hise Ingest by Legens Path. D WITHS-MEPLI Inget pursuators nathing Smines notch length O Optimization of corres poi I Identification notch line I Identify nucleo hos Ingest any nathing Of Smintain the original per	Epore see	Name oriented pro- Saport curve precision 6 V-shaped not ppend node 50 Automat nucleur sheet 17 Event	ic sheek of putter	Short nation Short Properties Of Audia File indices	(C. IIII. (Ex)	e so	Of colors	Stone of cutting	cording to col.
Tapers ext. Lise Tapers by Legres Path.   William service Leges powerfur satisfy Resistent satisfy Delinization of curve poi Lifestification of curve poi Lifestification satisfies Lifestification satisfies Lifestification satisfies Lifestification the series Lifes	Epore see	Name oriented pro- Saport curve precision 6 V-shaped not ppend node 50 Automat nucleur sheet 17 Event	ic sheek of putter	Their nation their Properties. Out report of Author File indeed Sather	(C. IIII. (Ex)	•	Parish re-		cording to col.
Tapers ext. Lise Tapers by Legres Path.   William service Leges powerfur satisfy Resistent satisfy Delinization of curve poi Lifestification of curve poi Lifestification satisfies Lifestification satisfies Lifestification satisfies Lifestification the series Lifes	Epore see	Name oriented pro- Saport cores precision 6 V-obaged not ppend node 50 Automat nucleor sheet 17 Event	ic sheek of putter	Short nation Short Properties Of Audia File indices	(C. IIII. (Ex)	e so	Of colors	Stone of cutting	cording to col.



## Modular Design:

DF0604-MT

Simply load the 7" high capacity suction pile feeder or take a look at one of our many options for the MT line. Optional roll feeder, high capacity inline roll feeder, and rewinders are available for roll to roll customers. The MT series digital die cutters comes with a roll away output tray and adjustabled guides to make feeding and collecting finished products a breeze.

## **SOFTWARE**

The supplied Sinajet program includes numerous operation modes and data interchange with the work table and the CCD camera. This enabled a seemless one step process for projects read in barcode and allows for perfect registration with the built in mark reader.







Dual RCT : Rotary Cutting Tools cuts up to 1.8mm



RST: Rotary Score/Perf Tool



ACT :
Active Circular Tool
cuts up to 1.8mm

ECT:
Electronic
Cutting Tool
cuts up to 6mm



EOT: Electronic Oscillating Tool Up to 10mm







## Scan to watch the DF0604-MT product video

Specifications	DF0604-MT	DF0906-MT	DF1007-MT		
Feeder pile height capacity	180 mm / 7"	180 mm / 7"	180 mm / 7"		
Max. Sheet Size (Autofeed)	680 mm x 420 mm / 26.8" x 16.5"	1000 mm x 700 mm / 39.4 ' x 27.5"	1010 mm x 720 mm / 39.75" x 28.3"		
Max. Cutting Area	600 mm x 400 mm / 23.6"x15.75"	900 mm x 600 mm / 35.4 x 23.6"	1000 mm x 700 mm / 39.4" x 27.5"		
Max. Cutting Speed	1,000 mm/second	1,000 mm/second	1,000 mm/second		
Cutting Thickness	Up to 10 mm	Up to 10 mm	Up to 10 mm		
Recommended cutting material	Cardstock, Paper, Labels, Foam Board	Cardstock, Paper, Labels, Foam Board	Cardstock, Paper, Labels, Foam Board		
	ABS, Paper and Plastic Corrugated	ABS, Paper and Plastic Corrugated	ABS, Paper and Plastic Corrugated		
Number of tool locations	4	4	4		
Standard tools included	Pen, RST (rotary score/perf tool)	Pen, RST (rotary score/perf tool)	Pen, RST (rotary score/perf tool)		
	ACT (active circular tool) fabric and textile cutting	ACT (active circular tool) fabric and textile cutting	ACT (active circular tool) fabric and textile cutting		
	Dual RCT (rotary cut tool) cuts up to 1.8 mm	Dual RCT (rotary cut tool) cuts up to 1.8 mm	Dual RCT (rotary cut tool) cuts up to 1.8 mm		
	ECT (electronic cut tool) cuts up to 6 mm	ECT (electronic cut tool) cuts up to 6 mm	ECT (electronic cut tool) cuts up to 6 mm		
Oscillating Knife Option	EOT (electronic oscillating tool) cuts up to 10 mm	EOT (electronic oscillating tool) cuts up to 10 mm	EOT (electronic oscillating tool) cuts up to 10 mm		
Active Circular Knife Option (fabric)	Yes	Yes	Yes		
Roll feed option	Yes	Yes	Yes		
Infrared anti-collision option	Yes	Yes	Yes		
Compressor required	Yes, built in	Yes, built in	Yes, built in		
Cutting and Camera Software	Sinajet Control Center	Sinajet Control Center	Sinajet Control Center		
QR Code Reader	Yes	Yes	Yes		
Barcode Reader	Yes	Yes	Yes		
CCD Camera Positioning	Yes	Yes	Yes		
Cutting Tolerance	+/- 0.1mm	+/- 0.1mm	+/- 0.1mm		
Min. Paper Weight	80 gsm/70 lb. text	80 gsm/70 lb. text	80 gsm/70 lb. text		
Dimensions	3123 (L) x 1090 (W) x 1170(H) mm	3882 (L) x 1250 (W) x 1175(H) mm	3934 (L) x 1350 (W) x 1065 (H) mm		
	123" (L) x 43" (W) x 46 "(H)	153" (L) x 49 (W) x 46 (H)	155" (L) x 53 (W) x 42 (H)		
Machine weight	450 kg / 990 lbs	500 kg / 1100 lbs	660 kg / 1455 lbs		
Warranty	1 year parts and electronics	1 year parts and electronics	1 year parts and electronics		



2817 Cedar Street Philadelphia PA, 19130 (215) 425-0300