



KEY FEATURES:

- Slit, cut, crease or perf in a single pass
- 150-350 gsm (100 lb text - 16 pt)
- Interchangeable crease or perf dies
- Full or partial cross perf
- Up to 32 crease/perfs in one pass
- Register mark cut compensation
- Preset programs and job memory for quick job changeover
- Manual cut/crease input option for custom jobs
- Easily change slitting formats without removing tools

<i>Electrical</i>	110V, 50/60 Hz, 15A
<i>Paper Weight</i>	150- 350 gsm
<i>Stock Input Size</i>	Min- 8.2" x 8.2" Max- 13" x 26"
<i>Finished Output Size</i>	Min- 2" x 1.8" Max- 13" x 26"
<i>Crease/Perforate</i>	0-32 per pass
<i>Minimum Gap between Crease</i>	0.1 mm
<i>Display and Operation</i>	6" colour touchscreen
<i>Feed</i>	2" vacuum pile feeder
<i>Image shift compensation</i>	Cut compensation (Y axis)
<i>Gutter Slit</i>	9.5mm/ 0.375" 3/8"
<i>Gutter Cut</i>	0mm or 3mm - 15mm







Established 1902

2817 CEDAR ST.
PHILADELPHIA, PA 19134
(215) 425-0300
WWW.NORTHERNMACHINE.COM

While every effort was made at time of publication to ensure accuracy, Graphic Whizard will not be liable for omissions or errors. Specifications and information are subject to change without notice. Actual results are dependent upon application. Paper stock, print engine used and environmental conditions will affect results.