

HLA-2301 AUTOMATIC LAMINATOR

High-Speed, Commercial-Grade, Fujipla Laminator!

The newest, commercial-grade Fujipla laminator by Dry-Lam has everything you know and love about the previous ALM line for automatic feeding, laminating, trimming, and stacking sheets, but is now faster and better with improved features and functionality! Laminating up to 68" per minute, it is 25% faster than the ALM3230.




Width: 13"

New & Improved!



Simple-slide paper
size adjustment



Improved film roll
installation



Upgraded multi-thick-
ness feed tray



Easy-to-use Color
Screen & Controls

Recommended Film*

- ▶ 1.5 mil Gloss
- ▶ 3.0 mil Gloss
- ▶ 3.0 mil Matte
- ▶ 5.0 mil Gloss

*Additional options may be available.
Contact sales for more info.





FEATURES

- ▶ Ultra-quick warm-up time of less than 5 minutes
- ▶ Automatic single or double-sided lamination
- ▶ 2 Automatic trim options
 - Flush-cut: precise, micro-adjustable with \pm 3mm margin adjust
 - Border-cut: custom-sealed options with 4-sided trim uniformity
- ▶ Hands-free, automatic feed tray
- ▶ Simple operation with specially encoded film for auto settings

SPECIALLY FORMULATED FILM

- ▶ Strong adhesion with no peeling or bubbling, even on flush-cut sheets
- ▶ Proprietary chip-reading design
- ▶ Automatically sets to the correct temperature for the film in use
- ▶ Includes stand with waste basket to collect scraps

Model	HLA-2301
Laminating Width	12.6"
Speed	68" per minute
Film Thickness	1.5 - 10 mil film (10 mil single-side only)
Laminating Thickness	16 mil, 17lb - 100lb cover
Heat Type	Heated Rollers
Temperature Range	170 - 270°F
Warm-up Time	Less than 5 minutes
Paper Sizes	8.5"x5.5", 8.5"x11", 11"x17", 12"x18", 13"x19"
Paper Feed Capacity	200 Sheets
Trimming Methods	Flush Cut or Border Cut
Operation Panel	Color LCD Display
Power Supply	100-240 VAC, 50-60Hz
Dimensions (LxWxH)	48" x 23.5" x 44"
Weight	Laminator: 163 lbs